



INSTRUMENT
APPROACH CHARTAD ELEV 767 FT
THR 31 ELEV 767 FT
HGT RELATED TO AD ELEV
VAR 4° EWIEN RADAR 134.675
TFI 118.525
VÖSLAU AD 118.605**MISSED APPROACH:** AT AV807 TURN RIGHT TO MOVOS; CLIMB TO 3000 FT AMSL AND HOLD.

NOTE: MISSED APPROACH SPEED IS LIMITED TO MAX IAS 120 KT !

OCA (OCH) IN FT	A	B	AV806 to AV807 - DISTANCE 3.6 NM						
				GS (KT)	80	100	120	140	
LNAV	1580 (820)		AV806 - AV807	MIN : SEC	2:42	2:10	1:48	1:33	
			Rate of descent (6.5%)	FT / MIN	530	660	790	920	
				DIST in NM to AV807	3	2			
VFR-PART: SEE CHART FOR VFR-FLIGHTS (LOAV AD 2.24-7-2)			ALT (HEIGHT)	2770 (2003)	2370 (1603)				

Instrument Approach Procedure Coding Table Vöslau RNAV (GNSS) A														
Path Terminator	Waypoint				Course/ Track ° MAG (° True)	DIST NM	Turn Direction	Constraints		Navigation Specification				
	Identifier	Type	Flyover	Coordinates				Level	Speed					
IF	MOVOS	IAF	no	N475440.60 E0162614.08				A3000+		RNP APCH				
TF	AV806	FAF	no	N475518.25 E0162339.30	286° (289.9°)	1.8		A3000+		RNP APCH				
TF	AV807	MAPt	yes	N475631.21 E0161838.45	286° (289.9°)	3.6				RNP APCH				
DF	MOVOS	MAHF	no	N475440.60 E0162614.08			right	A3000+	K120-	RNP APCH				
RNAV Holding														
Holding Point	Inbound Track ° True	Inbound Track ° MAG	Turn Direction	MAX IAS	Minimum Holding Altitude FT MSL / FL		Time	DIST NM	Remarks					
MOVOS	003.6°	360°	left	K120-	A3000		1 MIN							
THR Coordinates														
RWY 13	N475802.51 E0161521.87													
RWY 31	N475742.77 E0161556.97													